

**2008 Yamaha FX Nytro RTX Snowmobile - \$6,295**

*5,900 MILES*

Purchased new in 2009. New exhaust gaskets recently installed. Snowmobile has always been 100% reliable and is in excellent shape. Well maintained.

96 Woody's Gold Digger Carbide Traction Master studs  
Woody's Slim Jim Dooly 6" Trail Runners



<p><b>Engine</b>  Type / Displacement / cc Four-stroke, 1049cc  Cylinders Three  Horsepower Class 130 HP  Cooling Liquid  Bore &amp; Stroke / mm 82.0 X 66.2  Intake Design 2 Valves  Ignition Digital T.C.I. w/Throttle Position Sensor  Carburetion 41mm Mikuni, Fuel Injection  Rear Exhaust  Clutch / Transmission YVXC, Variable Ratio  Disc. Brake Type 4 Piston Hydraulic with Lightweight Disc</p> <p><b>Chassis</b>  Front Suspension Independent, Double Wishbone  Front Shocks Fox FLOAT Air Shock Aluminum  Front Travel / in. N/A  Ski Type Lightweight Plastic, Saddleless Design  Carbide Ski Runners Standard  Stabilizer Bar Standard, Linear Ratio  Rear Suspension Dual Shock Pro  Rear Shocks 40mm HPG w/reservoir, dual-clicker / 40mm HPG w/reservoir, dual-clicker adjustable  Rear Travel / in. 14.5"</p>	<p><b>Dimensions</b>  Overall Length / in. 108.5"  Overall Width / in. 48"  Overall Height / in. 42.9"  Track/Width x Length x Height / in. 15" X 121" X 1.25"  Camoplast Rip Saw  Estimated Dry Weight 513 lbs. / 520 lbs. (reverse model)  Ski Stance (ctr. to ctr.) in. 41.3"  Fuel Capacity / Gal. 7.4  Fuel Type Regular Unleaded  Oil Capacity / Qts. 3, Dry Sump  Engine Oil Type Yamalube 4, 0w-30, Cold Weather Formula</p> <p><b>Features</b>  Electric Start Standard  Reverse  Hand &amp; Thumb Warmers To-the-end, 10-position adjustable  Seating Capacity One  Tunnel Protectors Standard  Headlight Watts, Type 60/55W Halogen x 2  High Beam Indicator Standard  Oil &amp; Temp Light Standard  Fuel Gauge Type Electric (LCD), Low Fuel Warning Light  Speedometer Standard (LCD, Digital)  Odometer Standard (Large LCD Display)  Tripmeter Standard, Backlit (LCD)  Tachometer Standard, Backlit (LCD)</p>
-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Contact 585-455-4429**